



Solius/Solius Wi-Fi

EXTENSIVE HEAT PANEL WITH WEEKLY PROGRAMMING AND HOMOGENEOUS HEAT SPREAD







COMFORT

- Instantaneous feeling of warmth & homogeneous heat spread
- Easy prog: 24h/7, program your device according to your life rhythm for greater comfort & savings
- Extensive heat panel with black painted extruded aluminium heating element with wide heating surface
- Ultimate safety due to Class II, IP 24 protection and dual electric insulation
- · Anti-tilt system and automatic overheating safety device

SAVINGS

- · High-precision electronic thermostat
- Up to 25% energy savings*
- ErP-compliant

USER-FRIENDLINESS

- Ergonomic LCD digital controls
- 2 modes: Manual/Prog
- ASP (Anti-Staining Process) to reduce staining on wall and on equipment
- · Easy to install: H-shaped vertical support
- · Model with standing kit and plug (optional)

DESIGN

- Slim space-saving design for better integration into your home
- · Colour: White (RAL 9016)
- Back plate colour: Anthracite (RAL 7021)

WI-FI CONNECTIVITY**

- Remote piloting via the Cozytouch application (available on Google Play and Apple Store)
- Electricity consumption follow-up
- · Comfort and savings management
- Programming modes

EXTENSIVE HEAT PANEL

750 TO 2000 W





Energy savings











LCD digital controls

Remote piloting via
Cozytouch application

Technology

Heating element type





Solius/Solius Wi-Fi



- 3 Extruded aluminium heating element
- 4 Room temperature sensor
- 5 Anti-tilt system
- 6 Overheating safety device





- 1 Room & set temperature and active mode display (2 modes: Manual/Prog)
- 2 Navigation buttons
- 3 Access to menu/validation



- $^{\bullet}$ Manual mode: Allows to set up the device at the desired temperature from Off to 30 $^{\circ}\text{C}.$
- Prog mode: Allows to set up to 3 periods of Comfort temperature by day (24h) over 7 days. Possibility to copy a daily programme on other days of the week.

INSTALLATION DIMENSIONS





TECHNICAL DATA

OUTPUT (W)	DIMENSIONS (mm)						NET WEIGHT
	WIDTH (W)	HEIGHT (H)	DEPTH (D)	Α	B1	B2	(Kg)
750	527	477	129	269	256	158	5.2
1000	601	477	129	343	256	158	5.8
1500	823	477	129	565	256	158	7.8
2000	1045	477	129	787	256	158	9.2

C€ - Classe II - IP 24