zehnder
always the best climate

Zehnder Aura Bow

Product data sheet



Zehnder Aura Bow

Large spaces between the tubes and curved lines. Every detail of Zehnder Aura Bow is perfectly designed with modern bathrooms in mind. The decorative radiator for hot water central heating is available in white and with a high-quality chrome finish.


Benefits

- D-profile header tube creates harmonious design
- Ample spaces between tubes make cleaning easy
- Generous spaces between the tubes convenient for hanging towels
- Elegant design in high-quality chrome
- Small radiator depth ideal for narrow bathrooms

Special benefits for hot water operation

- Flexible installation through right and left connection options
- Available with Zehnder Vario connection fitting for an unobtrusive and elegantly concealed connection system
- Flexible installation due to 50mm centre connections

Model overview



L = length
WA = wall clearance

Dimensions in mm

Connection to hot water central heating system or for dual energy operation

Painted version

Model	H	L	Thermal output				Classification electric heating element
			75/65/20 °C[1)]	70/55/24 °C	55/45/24 °C	55/45/20 °C	
	mm	mm	Watt	Watt	Watt	Watt	Watt
Connection from bottom							
PBTZ-080-050	775	496	357	261	163	193	300
PBTZ-120-050	1217	496	511	371	229	273	300
PBTZ-150-050	1469	496	629	455	280	334	600
PBTZ-180-050	1856	496	786	568	349	417	600
PBTZ-080-060	775	595	420	307	192	228	300

H = height, L = length
1) Nominal heat output according to EN 442

V20180720, SI_en, subject to change without notice

Zehnder Aura Bow

Connection to hot water central heating system or for dual energy operation

Painted version

PBTZ-120-060	1217	595	595	431	266	317	600

Model	H	L	Thermal output				Classification electric heating element
			75/65/20 °C[1)]	70/55/24 °C	55/45/24 °C	55/45/20 °C	
	mm	mm	Watt	Watt	Watt	Watt	Watt
PBTZ-150-060	1469	595	737	534	330	393	600
PBTZ-180-060	1856	595	922	667	410	489	900
Central connection 50 mm							
PBTZ-080-050-05	775	494	357	261	163	193	300
PBTZ-120-050-05	1217	494	511	371	229	273	300
PBTZ-150-050-05	1469	494	629	455	280	334	600
PBTZ-180-050-05	1856	494	786	568	349	417	600
PBTZ-080-060-05	775	595	420	308	193	229	300
PBTZ-120-060-05	1217	595	595	431	266	317	600

Chrome-plated version

Model	H	L	Thermal output				Classification electric heating element
			75/65/20 °C[1)]	70/55/24 °C	55/45/24 °C	55/45/20 °C	
	mm	mm	Watt	Watt	Watt	Watt	Watt
Connection from bottom							
PBTCZ-080-050	775	494	229	164	99	119	-
PBTCZ-120-050	1217	494	331	236	142	171	300
PBTCZ-150-050	1469	494	406	290	175	210	300
PBTCZ-180-050	1856	494	514	367	221	266	300
PBTCZ-080-060	775	595	274	198	121	145	-
PBTCZ-120-060	1217	595	388	278	168	202	300
PBTCZ-150-060	1469	595	481	344	208	250	300
PBTCZ-180-060	1856	595	604	431	260	313	600
Central connection 50 mm							
PBTCZ-080-050-05	775	494	229	164	99	119	-
PBTCZ-120-050-05	1217	494	331	236	142	171	300
PBTCZ-150-050-05	1469	494	406	290	175	210	300
PBTCZ-180-050-05	1856	494	514	366	220	265	300
PBTCZ-080-060-05	775	595	274	198	121	145	-
PBTCZ-120-060-05	1217	595	388	278	168	202	300
PBTCZ-150-060-05	1469	595	481	344	208	250	300

H = height, L = length
1) Nominal heat output according to EN 442

V20180720, RAD_DAS, SI_en, subject to change without notice

Zehnder Group Deutschland GmbH · Sales International · Almweg 34 · 77933 Lahr · Germany
T +49 7821 586-392 · F +49 7821 586-406 · sales.international@zehndergroup.com · www.international.zehnder-systems.com