
Electric storage water heater

POC Luna inox


Water heater for wash basin with the tank made of stainless steel




Application



POC.D Luna inox (pressurized connection to any type of mixer tap)



POC.G Luna inox (pressurized connection to any type of mixer tap)



POC.Gb Luna inox (with a mixer tap and fittings)

Most important advantages



Stainless steel tank
Resistant to corrosion, no need to use an anode.



The use of 2000W immersion heater provides very short heating time:

- 5 liters in 5.5 min
- 10 liters in 11 minutes (water heating 10-40°C)




Energy efficiency class A
Very low energy losses



Temperature range from 20-70°C

Dimensions



Max supply water pressure	0,6 MPa
Water connection	Gz 1/2"
Safety class	IP 24
Energy efficiency class	A

Size	A	B	C
POC-5	427	285	163
POC-10	470	329	239

Technical data

Type	Rated power / rated value	Capacity (l)	Heating time Δt = 30°C (min.)
POC.D-5 LUNA INOX	2 kW / 230V	5	5,5
POC.G-5 LUNA INOX	2 kW / 230V	5	5,5
POC.Gb-5 LUNA INOX	2 kW / 230V	5	5,5
POC.D-5 600W INOX	0,6 kW / 230V	5	18
POC.G-5 600W INOX	0,6 kW / 230V	5	18
POC.Gb-5 600W INOX	0,6 kW / 230V	5	18
POC.D-10 LUNA INOX	2 kW / 230V	10	11
POC.G-10 LUNA INOX	2 kW / 230V	10	11
POC.Gb-10 LUNA INOX	2 kW / 230V	10	11
POC.D-10 600W INOX	0,6 kW / 230V	10	36
POC.G-10 600W INOX	0,6 kW / 230V	10	36
POC.Gb-10 600W INOX	0,6 kW / 230V	10	36